



540W MBB Half-cell Module JAM72S30 515-540/MR Series

Introduction

Assembled with 11BB PERC cells, the half-cell configuration of the modules offers the advantages of higher power output, better temperature-dependent performance, reduced shading effect on the energy generation, lower risk of hot spot, as well as enhanced tolerance for mechanical loading.



Higher output power



Lower LCOE




Less shading and lower resistive loss



Better mechanical loading tolerance

Superior Warranty

- 12-year product warranty
- 25-year linear power output warranty




■ JA Linear Power Warranty ■ Industry Warranty

Comprehensive Certificates

- IEC 61215, IEC 61730, UL 61215, UL 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- OHSAS 18001: 2007 Occupational health and safety management systems
- IEC TS 62941: 2016 Terrestrial photovoltaic (PV) modules – Guidelines for increased confidence in PV module design qualification and type approval



MECHANICAL DIAGRAMS



Remark: customized frame color and cable length available upon request

SPECIFICATIONS

Cell	Mono
Weight	28.5kg±3%
Dimensions	2267±2mm×1123±2mm×40±1mm
Cable Cross Section Size	4mm ² (IEC) , 12 AWG(UL)
No. of cells	144(6×24)
Junction Box	IP68, 3 diodes
Connector	QC 4.10(1000V) QC 4.10-35(1500V)
Cable Length (Including Connector)	Portrait: 300mm(+)/400mm(-); Landscape: 1200mm(+)/1200mm(-)
Packaging Configuration	27pcs/Pallet, 540pcs/40ft Container

ELECTRICAL PARAMETERS AT STC

TYPE	JAM72S30 -515/MR	JAM72S30 -520/MR	JAM72S30 -525/MR	JAM72S30 -530/MR	JAM72S30 -535/MR	JAM72S30 -540/MR
Rated Maximum Power(Pmax) [W]	515	520	525	530	535	540
Open Circuit Voltage(Voc) [V]	49.29	49.41	49.53	49.65	49.78	49.90
Maximum Power Voltage(Vmp) [V]	41.15	41.38	41.61	41.84	42.06	42.29
Short Circuit Current(Isc) [A]	13.28	13.33	13.38	13.43	13.48	13.53
Maximum Power Current(Imp) [A]	12.52	12.57	12.62	12.67	12.72	12.77
Module Efficiency [%]	20.2	20.4	20.6	20.8	21.0	21.2
Power Tolerance	0~+5W					
Temperature Coefficient of Isc(α _{Isc})	+0.045%/°C					
Temperature Coefficient of Voc(β _{Voc})	-0.275%/°C					
Temperature Coefficient of Pmax(γ _{Pmp})	-0.350%/°C					
STC	Irradiance 1000W/m ² , cell temperature 25°C, AM1.5G					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.They only serve for comparison among different module types.

ELECTRICAL PARAMETERS AT NOCT

TYPE	JAM72S30 -515/MR	JAM72S30 -520/MR	JAM72S30 -525/MR	JAM72S30 -530/MR	JAM72S30 -535/MR	JAM72S30 -540/MR
Rated Max Power(Pmax) [W]	389	393	397	401	404	408
Open Circuit Voltage(Voc) [V]	45.80	45.93	46.05	46.18	46.31	46.43
Max Power Voltage(Vmp) [V]	37.94	38.15	38.36	38.57	38.78	38.99
Short Circuit Current(Isc) [A]	10.89	10.93	10.97	11.01	11.05	11.09
Max Power Current(Imp) [A]	10.26	10.30	10.35	10.39	10.43	10.47
NOCT	Irradiance 800W/m ² , ambient temperature 20°C,wind speed 1m/s, AM1.5G					


*For NexTracker installations ,Maximum Static Load, Front is 1800Pa while Maximum Static Load, Back is 1800Pa.

OPERATING CONDITIONS


Maximum System Voltage	1000V/1500V DC
Operating Temperature	-40 °C ~+85 °C
Maximum Series Fuse	20A
Maximum Static Load,Front* Maximum Static Load,Back*	5400Pa(112lb/ft ²) 2400Pa(50lb/ft ²)
NOCT	45±2 C
Safety Class	Class II
Fire Performance	UL Type 1

CHARACTERISTICS

Current-Voltage Curve JAM72S30-520/MR



Power-Voltage Curve JAM72S30-520/MR



Current-Voltage Curve JAM72S30-520/MR

